



MEG系列



MEG



一体式

MEG-CCL



一体式加过滤网

MEG-WGX



一体镶嵌化钨芯

TPC-WGX



钨钢芯

基本特性

- 喷射角度: 在20至275bar (kg) 工作压力下喷射弧度为5°至65°。
- 喷雾形状: 扇形喷雾, 喷射区域成线形。
- 液滴大小: 液滴大小为小到中等, 分布均匀, 压力和流量适用范围广。
- 材 质: 硬化不锈钢 (SS)。
- 特 点: 液柱流型在单位面积上提供最大的打击力;
内置导流叶片稳定紊流, 实现均匀喷雾分布。

基本参数

在指定的压力下(以bar为单位)。

喷嘴型号和喷射弧度																	流量 代码	流量 (L/min)																
TPC-WGX					1/4MEG					1/4MEG-WGX								20巴	25巴	35巴	40巴	45巴	60巴	80巴	100巴	140巴	170巴	200巴						
40°	50°	65°	80°	95°	110°	130°	0°	5°	15°	25°	40°	50°	65°	0°	5°	15°	25°	40°	50°	65°														
																						010	1.0	1.1	1.3	1.4	1.5	1.8	2.0	2.3	2.7	3.0	3.2	
																							015	1.5	1.7	2.0	2.2	2.3	2.6	3.1	3.4	4.0	4.5	4.8
																							020	2.0	2.3	2.7	2.9	3.1	3.5	4.1	4.6	5.4	5.9	6.4
																							025	2.5	2.8	3.4	3.6	3.8	4.4	5.1	5.7	6.7	7.4	8.1
																							030	3.1	3.4	4.0	4.3	4.6	5.3	6.1	6.8	8.1	8.9	9.7
																							035	3.6	4.0	4.7	5.0	5.4	6.2	7.1	8.0	9.4	10.4	11.3
																							040	4.1	4.6	5.4	5.8	6.1	7.1	8.2	9.1	10.8	11.9	12.9
																							045	4.6	5.1	6.1	6.5	6.9	7.9	9.2	10.3	12.1	13.4	14.5
																							050	5.1	5.7	6.7	7.2	7.6	8.8	10.2	11.4	13.5	14.9	16.1
																							055	5.6	6.3	7.4	7.9	8.4	9.7	11.2	12.5	14.8	16.3	17.7
																							060	6.1	6.8	8.1	8.6	9.2	10.6	12.2	13.7	16.2	17.8	19.3
																							065	6.6	7.4	8.8	9.4	9.9	11.5	13.3	14.8	17.2	19.3	21
																							070	7.1	8.0	9.4	10.1	10.7	12.4	14.3	16.0	18.9	21	23
																							075	7.6	8.5	10.1	10.8	11.5	13.2	15.3	17.1	20	22	24
																							080	8.2	9.1	10.8	11.5	12.2	14.1	16.3	18.2	22	24	26
																							085	8.7	9.7	11.5	12.3	13.0	15.0	17.3	19.4	23	25	27
																							090	9.2	10.3	12.1	13.0	13.8	15.9	18.3	21	24	27	29
																							095	9.7	10.8	12.8	13.7	14.5	16.8	19.4	22	26	28	31
																							100	10.2	11.4	13.5	14.4	15.3	17.7	20	23	27	30	32
																							110	11.2	12.5	14.8	15.9	16.8	19.4	22	25	30	33	35
																							115	11.7	13.1	15.5	14.6	17.6	20	23	26	31	34	37
																							120	12.2	13.7	16.2	17.3	18.3	21	24	27	32	36	39
																							125	12.7	14.2	16.9	18.0	19.1	22	25	28	34	37	40

0°=液柱流 如需订购特殊尺寸, 请与销售人员联系!

订购信息

MEG	-	1/4	-	SS	-	15	-	040	-	WGX
喷嘴型号		螺纹尺寸		材质代码		喷射角度		流量代码		钨钢芯

如需NPT螺纹接口, 请在喷嘴的接口尺寸前加字母“N”

通用喷嘴