




BB系列 标准型



BB外螺纹式

基本特性

- 喷射角度: 42°-120°
- 喷雾形状: 实心锥形喷雾, 喷射区域成圆形。
- 液滴大小: 液滴大小为小到中等, 分布均匀, 压力和流量适用范围广。
- 材 质: 黄铜 (BRASS)、不锈钢 (SS)、塑料 (PP/PVC/PTFE) 等。
- 特 点: 内部为叶片、大流量通道设计, 保证和控制喷雾的均匀分布。

应用范围

- 水充气 ·消防灭火 ·喷淋冷却 ·粉尘控制
- 金属处理 ·气体洗涤清洗和冷却

基本参数

·标准角

在指定的压力下 (以bar为单位)。

接口尺寸 (in.)	流量代码	孔径 (mm)	流量 (L/min)										喷射角度 (°)		
			0.5巴	1巴	1.5巴	2巴	3巴	4巴	5巴	6巴	7巴	10巴	0.5巴	1.5巴	6巴
1/8	1	0.79	-	0.44	0.54	0.62	0.74	0.85	0.94	1.0	1.1	1.3	-	58	53
	1.5	1.2	0.49	0.69	0.81	0.93	1.1	1.3	1.4	1.5	1.7	1.9	65	65	59
	2	1.2	0.65	0.92	1.1	1.2	1.5	1.7	1.9	2.0	2.2	2.6	43	50	46
	3	1.5	0.98	1.4	1.6	1.9	2.2	2.5	2.8	3.1	3.3	3.9	52	65	59
	3.5	1.6	1.1	1.6	1.9	2.2	2.6	3.0	3.3	3.6	3.9	4.5	43	50	46
	3.9	2.0	1.3	1.8	2.1	2.4	2.9	3.3	3.7	4.0	4.3	5.1	77	84	79
	5	2.0	1.6	2.3	2.7	3.1	3.7	4.2	4.7	5.1	5.5	6.5	52	65	59
1/4	6.1	2.3	2.0	2.8	3.3	3.8	4.5	5.2	5.7	6.2	6.7	7.9	69	74	68
	6.5	2.4	2.1	3.0	3.5	4.0	4.8	5.5	6.1	6.7	7.1	8.4	45	50	46
	10	3.2	3.3	4.7	5.4	6.2	7.4	8.5	9.4	10.2	11.0	13.0	58	67	61
3/8	12.5	3.2	4.1	5.8	6.8	7.7	9.3	10.6	11.8	12.8	13.7	16.2	69	74	68
	9.5	2.6	3.1	4.7	5.1	5.9	7.1	8.1	8.9	9.7	10.4	12.3	45	50	46
	15	3.6	4.9	6.9	8.1	9.3	11.2	12.7	14.1	15.4	16.5	19.4	64	67	61
	20	4.0	6.5	9.2	10.8	12.4	14.9	17.0	18.8	20	22	26	76	80	73
1/2	22	4.5	7.2	10.2	11.9	13.6	16.4	18.7	21	23	24	28	87	90	82
	16	3.5	5.2	7.4	8.7	9.9	11.9	13.6	15.1	16.4	17.6	21	48	50	46
	25	4.6	8.2	11.6	13.5	15.4	18.6	21	24	26	27	32	64	67	61
	32	5.2	10.4	14.7	17.3	19.8	24	27	30	33	35	41	72	75	68
	40	6.2	13.1	18.5	22	25	30	34	38	41	44	52	88	91	83
3/4	50	6.7	16.3	23.1	27	31	37	42	47	51	55	65	91	94	86
	2.5	4.9	9.6	12.7	15.9	18.2	22	25	28.5	30	32	38	48	50	46
	4.0	6.4	15.4	20	26	29	35	40	45	48	52	61	67	70	63
1	7.0	9.5	27	35	45	51	61	70	78	84	91	107	89	92	84
	4.2	6.0	16.2	21	27	31	37	42	48	51	54	64	48	50	46
	7.0	8.3	27	35	45	51	61	70	79	84	91	107	67	68	62
	8.0	9.5	31	40	51	58	70	80	90	97	104	122	72	81	82
	10	11.9	38	51	65	73	88	100	113	121	130	153	78	90	94
	12	11.9	46	60	77	87	105	120	135	145	155	183	89	92	84



· 广角

在指定的压力下(以bar为单位)。

接口尺寸 (in.)	流量 代码	孔径 (mm)	流量 (L/min)										喷射角度(°)		
			0.5巴	1巴	1.5巴	2巴	3巴	4巴	5巴	6巴	7巴	10巴	0.5巴	1.5巴	6巴
1/8	2.8W	1.6	-	1.2	1.5	1.7	2.0	2.3	2.5	2.7	2.9	3.5	116	120	102
	4.3W	2.0	-	1.9	2.3	2.6	3.1	3.5	3.9	4.2	4.5	5.4	116	120	102
	5.6W	2.4	1.8	2.5	3.1	3.4	4.0	4.6	5.1	5.5	5.9	7.1	116	120	102
	8W	2.4	2.6	3.6	4.4	4.8	5.8	6.6	7.2	7.8	8.4	10.1	116	120	103
1/4	10W	2.8	3.3	4.5	5.5	6.0	7.2	8.2	9.1	9.8	10.6	12.7	116	120	103
	12W	3.2	3.9	5.3	6.5	7.3	8.7	9.8	10.9	11.8	12.7	15.2	117	120	103
	14W	3.6	4.6	6.2	7.6	8.5	10.1	11.5	12.7	13.7	14.8	17.7	117	120	103
3/8	17W	4.0	5.6	7.6	9.3	10.3	12.3	13.9	15.4	16.7	18.0	21.6	117	120	103
	20W	4.4	6.6	8.9	10.9	12.1	14.5	16.5	18.1	19.6	21.2	25.3	117	120	104
	24W	4.8	7.9	10.7	13.1	14.5	17.3	19.7	22	24	25.9	31.0	117	120	104
	27W	5.2	8.9	12.0	14.7	16.3	19.5	22	24	26	28.1	33.6	117	120	106
1/2	30W	5.6	9.9	13.4	16.4	18.1	22	25	27	29	31.3	37.4	117	120	108
	35W	6.0	11.5	15.6	19.1	21	25	29	32	34	36.7	43.9	117	120	108
	40W	6.4	13.1	17.8	21.8	24	29	33	36	39	42.1	50.3	117	120	108
	45W	6.4	14.8	20	24.5	27	33	37	41	44	47.5	56.8	117	120	110
	50W	6.7	16.4	22	26.9	30	36	41	45	49	52.9	63.3	117	120	112
3/4	6W	9.9	23	31	37	42	51	58	63	69	74	89	115	120	112
1	11W	13.1	42	57	69	78	93	106	115	126	136	162	117	120	117
1-1/4	16W	15.5	62	83	100	113	135	154	168	184	199	238	118	121	119
1-1/2	24W	18.3	92	125	150	170	203	230	251	275	297	355	119	124	119
2	47W	25	181	245	293	333	398	451	492	539	582	695	120	124	119

如需订购特殊尺寸, 请与销售人员联系。

订购信息

BB	-	1/4	-	SS	-	10
喷嘴型号		螺纹尺寸		材质代码		流量代码

如需NPT螺纹接口, 请在喷嘴的接口尺寸前加字母“N”